



भारत सरकार

GOVERNMENT OF INDIA

केन्द्रीय लोक निर्माण विभाग

CENTRAL PUBLIC WORKS DEPARTMENT

दिल्ली दर अनुसूची

(भाग - 2)

DELHI SCHEDULE OF RATES

(Vol. 2)

2018



महानिदेशक, के.लो.नि.वि., नई दिल्ली के प्राधिकार के अधीन प्रकाशित
Published under the Authority of Director General, CPWD, New Delhi

Code No.	Description	Unit	Rate
26.26	<p>Providing & fixing false ceiling at all heights with GRG (Glass Fibre Reinforced Gypsum) false ceiling tiles of Size 595x595 mm of approved texture, design and patterns having moisture content less than 2%, humidity resistance of 99%, NRC0.50 to 0.75 as per IS 8225:1987, Non-combustible as per BS 476 (part 4)-1970 and light Code Description Unit Rate No. 429 SUB HEAD : 26.0 NEW TECHNOLOGIES AND MATERIALS reflectance of 85% (minimum) to be laid in true horizontal level suspended on interlocking metal T-Grid of hot dipped galvanised iron section of 0.33mm thick (galvanized @ 120 grams per sqm including both sides) comprising of main-T runners of size 15x32 mm of length 3000 mm, cross - T of size 15x32 mm of length 1200 mm and secondary intermediate cross-T of size 15x32 mm of length 600mm to form grid module of size 600 x 600 mm, suspended from ceiling using galvanised mild steel items (galvanizing @ 80 grams per sqm) i.e. 50 mm long, 8 mm outer diameter M-6 dash fasteners, 6 mm dia fully threaded hanger rod upto 1000 mm length and L-shape level adjuster of size 85x25x2 mm.</p> <p>Galvanised iron perimeter wall angle of size 24x24x0.40 mm of length 3000 mm to be fixed on periphery wall / partition with the help of plastic rawl plugs at 450 mm center to center and 40 mm long dry wall wood screws. The work shall be carried out as per specifications, drawing and as per directions of the Engineer-in-Charge.</p>		
26.26.1	With semi perforated 12 mm thick micro tegular edged GRG false ceiling tiles.	sqm	1572.85
26.26.2	With fully perforated 12 mm thick micro tegular edged or 10 mm thick square edged GRG false ceiling tiles.	sqm	1699.3